TORQ COATINGS

GARAGES • BASEMENTS • PATIOS

FLOOR CARE INSTRUCTIONS

1 CURING TIME

The minimum time suggested before allowing foot traffic is **AT LEAST 24 HOURS**. Before driving or moving heavy items back inside is **AT LEAST 48 HOURS**.

2 CLEAN UP SPILLS

Promptly clean up oil and other spills to maintain the appearance of your floor. While the surface is stain-resistant, it is not completely stain-proof.

3 AVOID SHARP/ HEAVY OBJECTS

Our coatings are highly abrasion resistant. However, dragging heavy or sharp objects can cause scratching or damage.

4 NO HARSH CHEMICALS

Harsh cleaners and certain solvents may harm the floor's color and finish. Avoid contact with brake fluid, battery acid, or any corrosive substances.

5 AVOID ABRASION

Our coatings provide exceptional abrasion resistance. However, repeated wear over time may lead to premature surface deterioration.

6 CLEAN SAFELY

Remove debris by sweeping, vacuuming, or blowing the surface. Lightly mist or rinse the floor with warm water and an Eco-friendly soap, such as Simple Green or Dawn Dish Soap. Finish by using a squeegee to remove the water and direct it outside.

IF IT'S GONNA BE TOUGH...
IT'S GOTTA BE TORQ

844.867.7846 • TorqCoatings.com